

Declaration of performance

DoP F602eco-CPR-280319

PRODUCT

Product Type:	Roomheaters fired by solid fuel
Type, batch or serial number:	Jøtul F 602 ECO
Intended use:	Roomheater burning solid fuel without water supply
Fuel	Wood logs

MANUFACTURER

٢	Name:	Jøtul AS
Þ	Adress:	Postboks 1411 1602 Fredrikstad, Norway
Т	elephone:	+47 69 35 90 00
E	mail:	post@jotul.no

CHECKS

1		
	According to AVCP:	System 3
	Notified body:	Danish Tecnological Institute
	NB-No:	1235
	Test report no:	300-ELAB-2394-EN rev.1
	Harmonized norm:	EN 13240:2003:AC:2006/A2:2004:AC:2007

SAFETY

Safety distance to combustible materials	Minimum distances [in mm]
	Rear = 300
	Sides = 500
	Front = 550
	Floor = 0
	Ceiling = 700
	Also see the installation instructions
Fire safety	Pass
Reaction to fire	A1
Risk of burning fuel falling out	Pass
Surface temperature	Pass
Electrical safety	-
Release of dangerous substance	х
Cleanability	Pass
Maximum water operating pressure	-
Mechanical resistance (to carry a chimney/flue)	х

ΕN

PERFORMANCE AND EMISSION

Essential characteristics	Performance
Emission of combustion products	Pass
со	[0,0906 %], 1132 mg/Nm ³
NOx	87 mg/Nm3
OGC	55 mg/Nm3
PM	25 mg/Nm3
Flue gas temperature at the measuring section at nominal	
heat output [in °C]	259
Flue gas outlet temperature at nominal heat output [in °C]	311
Thermal output	Pass
Nominal heat output	4,9 kW
Nominal space heat output	4,9 kW
Nominal water heat output	-
Energy efficiency	η [81%]
Durability	x

Declaration:

The performance of the product is in conformity with the declared performance.

This declaration of performance is issued under the sole responsibility of the manufacturer.

Signed on behalf of the manufacturer:

Espen Løkkevig

R&D Manager

(Name and function)

Fredrikstad, June 2019

99

(Signature)